



SOLARTDI

Tecnología inteligente Solar
Tecnología Ubicua

Poligono Industrial Romica
Avd A / Parcela8 / Nave3
02008 ALBACETE

TLF. 967616116

tdi@solartdi.com

www.solartdi.com

TARIFA DE PRECIOS

REFERENCIA	IMAGEN DE PRODUCTO	PARAMETROS	MODO DE FUNCIONAMIENTO	EMBALAJE	PVR €
DS5		1, Solar panel :10W 17% efficiency 2, LED :20pcs ,7W, 700lumens (Natural led color : Pure white) LED life span:+50000hrs 3, Charging Method : Solar power 4, Charging time :6-8hrs 5, Battery : 13200mah li-ion battery 6, Material : Aluminum Alloy+PC 7, IP level : 65 8, With PIR motion sensor and light sensor 9,Working Temperature: -25°C to 65°C 10,Product size : 276MM*390MM 11,Warranty: 24 Months	3Hrs Full bright + 20% brightness + PIR motion sensor till dawn (Any other lighting mode can be customized)	Standard Carton Packing Size : L420*W170*H355mm 20 GP: 1000pcs , 40GP: 2230pcs , 40HQ: 2720pcs 1piece/carton Net Weight : 5Kg Gross Weight:5.5Kg	195 €
DS12		1, Solar panel :18W 17% efficiency 2, LED :40pcs ,12W, 1200lumens (Natural led color : Pure white) LED life span:+50000hrs 3, Charging Method : Solar power 4, Charging time :6-8hrs 5, Battery : 26400mah li-ion battery 6, Material : Aluminum Alloy+PC 7, IP level : 65 8, With PIR motion sensor and light sensor 9,Working Temperature: -25°C to 65°C 10,Product size : 276MM*690MM 11,Warranty: 24 Months	3Hrs Full bright + 20% brightness + PIR motion sensor till dawn (Any other lighting mode can be customized) With DC Input .	Standard Carton Packing Size : L720*W170*H355mm 20GP: 635pcs , 40GP:1316 pcs , 40HQ: 1543pcs 1piece/carton Net Weight : 8.5Kg Gross Weight:9Kg	339 €
DS18		1, Solar panel :25W 17% efficiency 2, LED :60pcs ,20W, 2000lumens (Natural led color : Pure white) LED life span:+50000hrs 3, Charging Method : Solar power 4, Charging time :6-8hrs 5, Battery : 39600 mah li-ion battery 6, Material : Aluminum Alloy+PC 7, IP level : 65 8, With PIR motion sensor and light sensor 9,Working Temperature: -25°C to 65°C 10,Product size : 276MM*940MM 11,Warranty: 24 Months	3Hrs Full bright + 20% brightness + PIR motion sensor till dawn (Any other lighting mode can be customized) With DC Input .	Standard Carton Packing Size : L970*W170*H355mm 20GP :471pcs , 40GP:1081 pcs , 40HQ:1145pcs 1piece/carton Net Weight : 10.5Kg Gross Weight:11.5Kg	489 €
US30		1, Solar panel :50W 17% efficiency 2, LED :30W, 3000LM-3600LM (Natural led color : Pure white) LED life span:+50000hrs 3, Charging Method : Solar power 4, Charging time :6-8hrs 5, Battery : 325WH li-ion battery 6, Material : Aluminum Alloy+PC 7, IP level : 65 8, With Light sensor 9,Working Temperature: -25°C to 65°C 10,Product size :438MM*880MM 11,Warranty: 24 Months	High Power Solar charging , fast charging with long service time . Auto lighting when dark ,auto-off during daytime . 5hrs full bright + PIR until dawn With activated Switch	Standard Carton Packing Size : L980*W530*H250mm 20 GP: 217pcs , 40GP: 450pcs , 40HQ: 527 pcs 1piece/carton Net Weight : 15 Kg Gross Weight:16.5 Kg	637 €

TARIFA DE PRECIOS

REFERENCIA	IMAGEN DE PRODUCTO	PARAMETROS	MODO DE FUNCIONAMIENTO	EMBALAJE	PVR €
FAROLAS INTELIGENTES SOLARES MONOBLOCK GAMA ULTRA-SLIM					
US60		<p>1, Solar panel :80W 19% efficiency 2, LED :60W, 6000LM-7000LM (Natural led color : Pure white) LED life span:+50000hrs 3, Charging Method : Solar power 4, Charging time :6-8hrs 5, Battery : 651 WH li-ion battery 6, Material : Aluminum Alloy+PC 7, IP level : 65 8, With Light sensor 9,Working Temperature: -25°C to 65°C 10,Product size :438MM*1220 MM 11,Warranty: 24 Months</p>	<p>High Power Solar charging , fast charging with long service time . Auto lighting when dark ,auto-off during daytime . 5hrs full bright + PIR until dawn With activated Switch</p>	<p>Standard Carton Packing Size : L1170*W530*H250mm 20 GP: 180 pcs 40GP: 374 pcs , 40HQ: 438 pcs 1piece/carton Net Weight : 21.5 Kg Gross Weight:22.5 Kg</p>	875 €
US80		<p>Solar Panel :110W (High efficiency monocrystalline silicon) Battery : Lithium battery 3.7V 130AH Led Light : 80W (USA Bridgelux) , 8000-9600LM CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days PIR Working temp: -20°C +65°C IP65 Battery Lifetime : 1000cycle times Mounting height : 8-10M,Pole dia ≤80mm Space Between Lights : 28-38M Warranty : 3 years</p>		<p>Product size : 1410*438mm Package size: 150*53*25cm N.G/G.W (KG) 28/ 30KG</p>	898 €
US120		<p>Solar Panel :123W (High efficiency monocrystalline silicon) Battery : Lithium battery 3.7V 168AH Led Light : 100W (USA Bridgelux) , 10000-12000LM CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days PIR Working temp: -20°C +65°C IP65 Battery Lifetime : 1000cycle times Mounting height : 8-10M,Pole dia ≤80mm Space Between Lights : 28-38M Warranty : 3 years</p>		<p>Product size : 1520*438mm Package size: 162*53*25cm N.G/G.W (KG) 29/ 31KG</p>	969 €
Versión estándar de la serie E3 de farolas de LEDs todo en uno (diseño con acceso exterior para el reemplazo de la batería y del regulador tres modos de trabajo, logotipo LED, indicador LED)					
US30-E		<p>Solar Panel :43.2W (High efficiency monocrystalline silicon) Battery : Lithium battery 3.7V 57AH Led Light :30W (USA Cree) , 3000-3600LM CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days , Microwave Sensor Working temp: -20°C +65°C IP65 Battery Lifetime : 1000cycle times Mounting height :5-7M,Pole dia ≤60mm Space Between Lights :15-20M Warranty : 3 years</p>		<p>Product size : 890*328mm Package size: 100*40*20cm N.G/G.W (KG) 9/ 10KG</p>	399 €

TARIFA DE PRECIOS

REFERENCIA	IMAGEN DE PRODUCTO	PARAMETROS	MODO DE FUNCIONAMIENTO	EMBALAJE	PVR €
US40-E 		Solar Panel :55W (High efficiency monocrystalline silicon) Battery : Lithium battery 3.7V 73AH Led Light :40W (USA Cree), 4000-4800LM CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time : 12hrs 3-5days Microwave Sensor Working temp: -20°C+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :7-8M,Pole dia ≤80mm Space Between Lights :20-22M Warranty : 3 years		Product size : 1070*328mm Package size: 117*40*25cm N.G/G.W (KG) 12/ 13KG	475 €
US60-E 		Solar Panel :72W (High efficiency monocrystalline silicon) Battery : Lithium battery 3.7V 98AH Led Light :60W (USA Cree), 6000-7000LM CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time : 12hrs 3-5days Microwave Sensor Working temp: -20°C+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :8-9M,Pole dia ≤80mm Space Between Lights :25-28M Warranty : 3 years		Product size : 1500*328mm Package size: 160*40*25cm N.G/G.W (KG) 16/ 18KG	598 €
US80-E 		Solar Panel :80W (High efficiency monocrystalline silicon) Battery : Lithium battery 3.7V 120AH Led Light :80W (USA Cree), 8000-9600LM CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time : 12hrs 3-5days Microwave Sensor Working temp: -20°C+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :8-10M,Pole dia ≤80mm Space Between Lights :30-38M Warranty : 3 years		Product size : 1640*328mm Package size: 174*40*25cm N.G/G.W (KG) 19/ 21KG	777 €
Versión de alta configuración de la serie DS (logotipo LED, diseño de cajón para el reemplazo de la batería y el controlador, 32 modos de iluminación selección por control remoto, indicador LED). Producto patentado					
DS30-RC 		Solar Panel :43.2W (High efficiency monocrystalline silicon) Battery : Lithium battery 3.7V 66AH Led Light : 30W (USA Cree), 3000-3600LM CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time : 12hrs 3-5days Microwave Sensor Working temp: -20°C+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :5-7M,Pole dia ≤60mm Space Between Lights :15-20M Warranty : 3 years		Product size : 890*328mm Package size: 100*40*20cm N.G/G.W (KG) 9/ 10KG	469 €

TARIFA DE PRECIOS

REFERENCIA	IMAGEN DE PRODUCTO	PARAMETROS	MODO DE FUNCIONAMIENTO	EMBALAJE	PVR €
DS50-RC 		Solar Panel :50W (High efficiency monocrystalline silicon) Battery : Lithium battery 3.7V 75AH Led Light :40W (USA Cree) , 4000-4800LM CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days Microwave Sensor Working temp: -20°C+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :7-8M,Pole dia ≤80mm Space Between Lights :20-22M Warranty : 3 years		Product size : 1070*328mm Package size: 117*40*25cm N.G/G.W (KG) 15/ 16KG	569 €
DS60-RC 		Solar Panel :70W (High efficiency monocrystalline silicon) Battery : Lithium battery 3.7V 110AH Led Light :60W (USA Cree) , 6000-7000LM CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days Microwave Sensor Working temp: -20°C+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :8-9M,Pole dia ≤80mm Space Between Lights :25-35M Warranty : 3 years		Product size : 1115*438mm Package size: 122*40*25cm N.G/G.W (KG) 18/ 20KG	739 €
DS80-RC 		Solar Panel :90W (High efficiency monocrystalline silicon) Battery : Lithium battery 3.7V 130AH Led Light :80W (USA Cree) , 6000-7000LM CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days Microwave Sensor Working temp: -20°C+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :8-10M,Pole dia ≤80mm Space Between Lights 30-38M Warranty : 3 years		Product size : 1220*438mm Package size: 111*40*25cm N.G/G.W (KG) 22/ 24KG	897 €
RONDOPLAZA15		1, Solar panel :20W 17% efficiency 2, LED :15W, 1500lumens (Natural led color : Pure white) LED life span:+50000hrs 3, Charging Method : Solar power 4, Charging time :6-8hrs 5, Battery : 148WH li-ion battery 6, Material : Aluminum Alloy+PC 7, IP level : 65 8, With Light sensor 9,Working Temperature: -25°C to 65°C 10,Product size :Dia 530MM*227MM 11,Warranty: 24 Months	High Power Solar charging , fast charging with long service time . Auto lighting when dark ,auto-off during daytime . 5hrs full bright + Dim until dawn With activated Switch	Standard Carton Packing Size : L630*W630*H300mm 20 GP: 288pcs , 40GP: 577pcs , 40HQ: 701 pcs 1piece/carton Net Weight : 7.5 Kg Gross Weight:8.5 Kg	295 €
RONDORGB18		1, Solar panel :25W 17% efficiency 2, LED :18W, 1800lumens (Natural led color : Pure white) LED life span:+50000hrs 3, Charging Method : Solar power 4, Charging time :6-8hrs 5, Battery : 222WH li-ion battery 6, Material : Aluminum Alloy+PC 7, IP level : 65 8, With Light sensor 9,Working Temperature: -25°C to 65°C 10,Product size :Dia 530MM*227MM 11,Warranty: 24 Months	High Power Solar charging , fast charging with long service time . Auto lighting when dark ,auto-off during daytime . 5hrs full bright + Dim until dawn .With activated Switch , RGB Landscape led light with remote control, 7color adjustable . White led lighting and RGB led lighting switchable	Standard Carton Packing Size : L630*W630*H300mm 20 GP: 288pcs , 40GP: 577pcs , 40HQ: 701 pcs 1piece/carton Net Weight : 7.5 Kg Gross Weight:8.5 Kg	439 €



SOLARTDI

Tecnología inteligente Solar
Tecnología Ubicua

Poligono Industrial Romica
Avd A / Parcela8 / Nave3
02008 ALBACETE

TLF. 967616116

www.solartdi.com

tdi@solartdi.com

TARIFA DE PRECIOS

REFERENCIA	IMAGEN DE PRODUCTO	PARAMETROS	MODO DE FUNCIONAMIENTO	EMBALAJE	PVR €
RONDOKILLER18		1, Solar panel :25W 18V 17% efficiency 2, LED : White Leds 18W, Trap lamp 9W LED life span:+50000hrs 3, Charging Method : Solar power 4, Charging time :6-8hrs 5, Battery : 13AH 11.1V li-ion battery 6, Material : Aluminum Alloy+PC 7, IP level : 65 8, With Light sensor 9,Working Temperature: -25°C to 65°C 10,Product size : Dia 530MM*290MM 11,Warranty: 24 Months 12, Installation Height : 4-5Meters	RF Remote control Two Key to switch Led Lighting and mosquito killer function /Auto on at night/ auto off at daytime A type : White Led 18W 1800LM, 5hrs 100% full bright+30% dim light until dawn.Light control Lux 20 B Type: Mosquito killing function Light control lux :20 Timing : 5Hrs Water sensor: Stop work at rainy days	Standard Carton Packing Size : L630*W630*H300mm 20 GP: 288pcs , 40GP: 577pcs , 40HQ: 701 pcs 1piece/carton Net Weight : 7.5 Kg Gross Weight:8.5 Kg	699 €
FAROLA INTELIGENTE SOLAR MONOBLOCK CON CAMARA DE HD Y WIFI					
US15-CAM	 NUEVO	1, Solar panel :70W 18V 19% efficiency 2, LED : 15W 1650LM , LED life span:+50000hrs 3, Charging Method : Solar power 4, Charging time :6-8hrs 5, Battery : 521WH li-ion battery 6, Material : Aluminum Alloy+PC 7, IP level : 65 8, With Light sensor 9,Working Temperature: -25°C to 65°C 10,Product size : 438MM*1000MM 11,Warranty: 36 Months 12, Installation Height :4-6Meters	1,Network Camera: : 3MP (dpi) ; 2, Power supply voltage:DC12V±10% / 24W (V) ; 3,Minimum Illuminance 0.001 (Lux) Use requirements: the product must be covered by the wireless signal within the scope or directly plug the network cable; Solar led light will work at night and auto off at daytime . Camera will work day and night . (All the time keep working) .	Standard Carton Packing Size : L1100*W530*H250mm 20 GP: 193 pcs , 40GP: 400 pcs , 40HQ: 469 pcs 1piece/carton Net Weight : 17.5Kg Gross Weight:19 Kg	618 €
US30-CAM	 NUEVO	1, Solar panel :90W 18V 19% efficiency 2, LED : 30W 3600LM , LED life span:+50000hrs 3, Charging Method : Solar power 4, Charging time :6-8hrs 5, Battery : 651WH li-ion battery 6, Material : Aluminum Alloy+PC 7, IP level : 65 8, With Light sensor 9,Working Temperature: -25°C to 65°C 10,Product size : 438MM*1220MM 11,Warranty: 24 Months 12, Installation Height :5-7Meters	1,Network Camera: : 3MP (dpi) ; 2, Power supply voltage:DC12V±10% / 24W (V) ; 3,Minimum Illuminance 0.001 (Lux) Use requirements: the product must be covered by the wireless signal within the scope or directly plug the network cable; Solar led light will work at night and auto off at daytime . Camera will work day and night . (All the time keep working) .	Standard Carton Packing Size : L1320*W530*H250mm 20 GP: 156 pcs , 40GP: 324 pcs , 40HQ: 380 pcs 1piece/carton Net Weight : 25.5Kg Gross Weight:26.5 Kg	999 €

DETALLES

Todos los productos pasan doble control de calidad; en fábrica y a la recepción en España.

- Las muestras (menos de 5 u.) se servirán en 6/8 días tras la confirmación del pago.
- Los grandes pedidos se pagarán un 50% a la confirmación del pedido y un 50% a la expedición por flete marítimo (35 días)
- Tenemos una propuesta de financiación con Renting tecnológico, a disposición del cliente final que puede incluir montaje y mantenimiento.
- GARANTÍA 2 Años, El servicio se realizará en España en la delegación del fabricante
- 5- POSIBILIDAD OEM.