



SOLARTDI

Antonio Tornero Jimenez
967616116 / 637449028
Pol.Ind.Romica-Avd A- Parcela 8-3
02008 Albacete

tdi@solartdi.com

www.solartdi.com



TARIFA ALUMBRADO SOLAR INTELIGENTE MONOBLOCK QPP

MODELO	IMAGEN	ESPECIFICACIONES TECNICAS	PVP	EMBALAJE	EJEMPLO DE INSTALACION
TDI-32P		Solar Panel :20W (High efficiency monocrystalline silicon) Battery : 98WH Led Light :20W (Cree) , 160LM /W CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days , PIR +Remote Working temp: -20°C-+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :5-6M,Pole dia ≤60mm Space Between Lights :12-14M Warranty : 3 years	233,00 €	Product size : 520*328mm CTN :60*40*20CM G.W /N.W : 5.5/6KG 20FT: 580pcs , 40GP: 120pcs , 40HQ: 1410pcs	
TDI-33P		Solar Panel :35W (High efficiency monocrystalline silicon) Battery : 196WH Led Light :30W (Cree) , 160LM /W CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days , PIR +Remote Working temp: -20°C-+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :6-7M,Pole dia ≤60mm Space Between Lights :14-18M Warranty : 3 years	323,00 €	Product size : 710*328mm CTN :81*40*20CM G.W /N.W : 7/8KG 20FT: 430pcs , 40GP: 890pcs , 40HQ:1000pcs	
TDI-34P		Solar Panel :43.2W (High efficiency monocrystalline silicon) Battery: 228WH Led Light :40W (Cree) , 160LM /W CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days , PIR +Remote Working temp: -20°C-+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :6-7M,Pole dia ≤60mm Space Between Lights :20-25M Warranty : 3 years	394,00 €	Product size : 890*328mm CTN :100*40*20CM G.W /N.W : 9/10KG 20FT: 350pcs , 40GP: 725pcs , 40HQ:850pcs	
TDI-35P		Solar Panel :55W (High efficiency monocrystalline silicon) Battery : 261WH Led Light :50W (Cree) , 160LM /W CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days PIR +Remote Working temp: -20°C-+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :7-8M,Pole dia ≤80mm Space Between Lights :22-25M Warranty : 3 years	489,00 €	Product size : 1040*328mm CTN 1:112*40*13CM CTN 2: 42*20*22CM CTN 1 G.W /N.W : 9/9.5KG CTN2: G.W /N.W : 2.2/2.5KG 20FT: 350pcs , 40GP: 725pcs , 40HQ: 850pcs	
TDI-36P		Solar Panel :55W (High efficiency monocrystalline silicon) Battery : 293WH Led Light :60W (Cree) , 160LM /W CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days PIR +Remote Working temp: -20°C-+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :7-8M,Pole dia ≤80mm Space Between Lights :22-25M Warranty : 3 years	500,00 €	Product size : 1040*328mm CTN 1:112*40*13CM CTN 2: 42*20*22CM CTN 1 G.W /N.W : 9/9.5KG CTN2: G.W /N.W : 2.2/2.5KG 20FT: 350pcs , 40GP: 725pcs , 40HQ: 850pcs	



SOLARTDI

Antonio Tornero Jimenez
967616116 / 637449028
Pol.Ind.Romica-Avd A- Parcela 8-3
02008 Albacete

tidi@solartdi.com

www.solartdi.com



TDI Nuevas tecnologías

MODELO	IMAGEN	ESPECIFICACIONES TÉCNICAS	PVP	EMBALAJE	EJEMPLO DE INSTALACIÓN
TDI-37P		Solar Panel :55W (High efficiency monocrystalline silicon) Battery : Lithium battery 326WH Led Light :70W (Cree), 160LM /W CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days PIR +Remote Working temp: -20°C-+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :7-8M,Pole dia ≤80mm Space Between Lights :22-25M Warranty : 3 years	510,00 €	Product size : 1040*328mm CTN 1 :112*40*13CM CTN 2 : 42*20*22CM CTN 1 G.W /N.W : 9/9.5KG CTN2: G.W /N.W : 2.2/2.5KG 20FT: 350pcs , 40GP: 725pcs , 40HQ: 850pcs	
TDI-38P		Solar Panel :78W (High efficiency monocrystalline silicon) Battery : 391WH Led Light :80W (Cree), 160LM /W CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days PIR +Remote Working temp: -20°C-+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :8-9M,Pole dia ≤80mm Space Between Lights :25-28M Warranty : 3 years	615,00 €	Product size : 1490*328mm CTN 1 :158*40*13CM CTN 2 : 42*20*22CM CTN1: G.W /N.W : :14.2/14.7KG CTN2 G.W /N.W : 2.2/2.5KG 20FT: 280pcs , 40GP: 580pcs , 40HQ: 680pcs	
TDI-39P		Solar Panel :78W (High efficiency monocrystalline silicon) Battery : 456WH Led Light :90W (Cree), 160LM /W CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days PIR +Remote Working temp: -20°C-+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :8-9M,Pole dia ≤80mm Space Between Lights :25-28M Warranty : 3 years	635,00 €	Product size : 1490*328mm CTN 1 :158*40*13CM CTN 2 : 42*20*22CM CTN1: G.W /N.W : :14.2/14.7KG CTN2 G.W /N.W : 2.2/2.5KG 20FT: 280pcs , 40GP: 580pcs , 40HQ: 680pcs	
TDI-310P		Solar Panel :78W (High efficiency monocrystalline silicon) Battery : 521WH Led Light :100W (Cree), 160LM /W CCT : 6000-6500K (OEM Acceptable) Material: Aluminum Alloy (Oxidation) Charging time : 6-8H Working time: 12hrs 3-5days PIR +Remote Working temp: -20°C-+65°C IP65 Battery Lifetime : 1000cycle times Mounting height :8-9M,Pole dia ≤80mm Space Between Lights :25-28M Warranty : 3 years	655,00 €	Product size : 1490*328mm CTN 1 :158*40*13CM CTN 2 : 42*20*22CM CTN1: G.W /N.W : :14.2/14.7KG CTN2 G.W /N.W : 2.2/2.5KG 20FT: 280pcs , 40GP: 580pcs , 40HQ: 680pcs	

EL MODELO ESTANDAR SE PRESENTA CON CONTROL MANDO A DISTANCIA PARA LA SELECCIÓN DE 3 MODELOS DE ILUMINACIÓN

- 1> Descuento profesional variable en función de las condiciones EXW, FOB, CIF, DDU, DDP
- 2> Condiciones de pago; 30% para el inicio de la producción y 70% para embarque de la mercancía.
- 3>.Certificados; todas nuestras farolas estan certificadas CE, ROHS, FCC, ISO Estandares
- 4> Los precios incluye la farola completa y funcional pero no el soporte, pié/báculo
- 5>Posible personalización dem embalage, prestaciones de alumbrado y de cámara , Color Temperatura 2700-6500K a elección del cliente.

Para la customización del producto podemos ayudarle con el diseño y la traducción a otros idiomas. Igualmente podemos ofrecer formación de producto a sus equipos de ventas.